

# NGXS

## UNIDIRECTIONAL GATEWAY SPECS



Dimensions	17" (W) x 29"(L) x 1.75"(H) 43.2cm (W) x 73.7cm (L) x 4.4cm (H) 26.5lbs (12kg)
Operating Temperature	0°C ~ 50°C (32°F ~ 122°F)
Non-Operating Temperature	-20°C - 80°C (-4°F - 176°F)
Operating Relative Humidity	10% ~ 85% (non-condensing)
Non-Operating Relative Humidity	10% ~ 95% (non-condensing)
Maximum Output Power	300 Watts
AC Input Voltage	100-240V
Frequency	60/50Hz
Nominal Input Current	6-4 Amps
BTU	Max: 1020 BTU Nominal: 400 BTU
I/O Ports	2 x 10G RJ45 Ethernet (Data) 2 x 1G RJ45 (Audit) 2 x USB 3.0 port (keyboard/mouse) 2 x VGA (Display) Max throughput 10Gbps
Security	UEFI Secure Boot SELinux, Enforcing Mode Captive UI (no shell access) Two Knowledgeable Person Control (TKPC)
Standards	Common Criteria EAL 4+ ITSG-33/NIST 800-53 TEMPEST Zone 1 (211117CO1836Z1)