



UGW-100

UNIDIRECTIONAL GATEWAY



| | |
|---------------------------------|---|
| Dimensions | 17" (W) x 29"(L) x 1.75"(H) 43.2cm (W) x 73.7cm (L) x 4.4cm (H) 26.5lbs (12kg) |
| Operating Temperature | 0°C ~ 50°C (32°F ~ 122°F) |
| Non-Operating Temperature | -20°C - 80°C (-4°F - 176°F) |
| Operating Relative Humidity | 10% ~ 85% (non-condensing) |
| Non-Operating Relative Humidity | 10% ~ 95% (non-condensing) |
| Maximum Output Power | 300 Watts |
| AC Input Voltage | 100-240V |
| Frequency | 60/50Hz |
| Nominal Input Current | 6-4 Amps |
| BTU | Max: 1020 BTU Nominal: 400 BTU |
| I/O Ports | 2 x 10G RJ45 Ethernet (Data) 2 x 1G RJ45 (Audit) 2 x USB 3.0 port (keyboard/mouse) 2 x VGA (Display) Max throughput 8Gbps |
| Security | UEFI Secure Boot SELinux, Enforcing Mode Captive UI (no shell access) Two Knowledgeable Person Control (TKPC) |
| Standards | Common Criteria EAL 4+ NSA Approved ITSG-33/NIST 800-53 TEMPEST Zone 1 (211117CO1836Z1) |