



UGW-200



NGXS UGW-200 UNIDIRECTIONAL GATEWAY

Performance	Max throughput 20Gbps
Dimensions & Weight	17" (W) x 29"(L) x 1.75"(H) 43.2cm (W) x 73.7cm (L) x 4.4cm (H) 26.5lbs (12kg)
Operating Temperature	0°C ~ 50°C (32°F ~ 122°F)
Non-Operating Temperature	-20°C - 80°C (-4°F - 176°F)
Operating Relative Humidity	10% ~ 85% (non-condensing)
Non-Operating Relative Humidity	10% ~ 95% (non-condensing)
Maximum Output Power (Total)	600 Watts
AC Input Voltage	100-240V
Frequency	60/50Hz
Nominal Input Current (Total)	12-8 Amps
BTU (Total)	Max: 2040 BTU Nominal: 800 BTU
I/O Ports	For each of Black and Red: 25Gbps SFP (Data) 10Gbps RJ45 (Audit) 2 x USB 3.0 port (keyboard/mouse) VGA (Display)
Security	UEFI Secure Boot SELinux, Enforcing Mode Captive UI (no shell access) Two Knowledgeable Person Control (TKPC)
Standards	Common Criteria EAL 4+ ITSG-33/NIST 800-53